

RBH fingerprint with keyboard + MiFARE DESFire card reader now compatible with RBH's NFC & Bluetooth mobile credentials

RBH-BFR-350-DNB SERIES

The RBH-BFR350 Fingerprint reader is integrated to all RBH software platforms for easy cardholder enrollment. The BFR-350 is compatible with the technologies most commonly used nowadays, now with the power of blueLINE Mobile credentials. With IP65 rating with 9500 template capacity and many operating modes.



OSDP V18V2

Several verification ontions

+9.500 fingerprint templates

Fast matching speed

NFC & Bluetooth (BLE) mobile credential compatible

Fully integrated with





Integra 32[™]

With the technology of



Specifications	
Verification options	Credential, Finger, PIN, Credential + Finger, PIN+Finger, Credential+PIN
Verification time	Less Than 2.0 Seconds (1:1 Verification Mode)
Autentication Speed	Less than 4.0 Seconds
Templates/Users	Up to 9,500 / 4750
Technology	DESFire (EV1, EV2 & V3) / Bluetooth / NFC
Integrated Reader	SECTOR / CSN for MiFARE Classic / Plus / DESFire EV1/2/3 (RBH-BFR-350-D for sector & RBH-BFR-350-S for CSN)
PC to Reader / Panel to Reader	Ethernet (CAT5) / Wiegand (6 Cond. Shielded 18 AWG)
Communication data	
Communication method	Wiegand, TCP/IP
Communication environment	LAN / WAN
Ethernet Interface	10/100M Base-T, Auto Crossover
Read Range	2 cm - 20 cm dependent on credential
Frequency	13.56 MHz / Bluetooth
Electrical data conditions	
Operation voltage	DC 12~15 V, 1A
Operation temperature	0°C to 55°C (32°F to 131°F)
Operation humidity	5% - 95% RH
Anti-Tampering switch	Yes
Physical data	
Dimensions	145 x 125 x 33 mm - (5.7 x 4.9 x 1.3 in)
Rating	IP-65
Weight	12 oz (340 gr)
Certifications	FC (E) Pending A Pending

Order:

RBH-BFR-350-DNB-D for sector RBH-BFR-350-DNB-S for CSN





RBH Access Technologies, Inc. 2 Automatic Road, Suite 108 Brampton ON L6S 6K8, Canada

> 1-905-790-1515 1-905-790-3680

info@rbh-access.com





