



Touch Screen Face Recognition **RBH-BFR-FACE15-DNB series**

Innovative system integrated Face readers by RBH are available with Mifare, Desfire, NFC & Blue-tooth (BLE) readers.

www.rbh-access.com

RBH-BFR-FACE15-DNB SERIES

Users will benefit from its unparalleled performance, ease of use, precision and fast matching speed. This Face reader features a highly accurate. The user will also benefit from the advanced matching algorithm and audio-visual indications for acceptance & rejection of Face.



Compact design

OSDP

10.000 user face detection

Dual camera fast recognition

User friendly touch screen

Fully integrated with



With the technology of



Specifications

Processor	ARM based 32 bits
Verification mode	Face/ Pin code/ Card/ Mobile
Face / Card capacity	10.000
System log	10,000
Web Base Management	Yes
Verification speed	< 0.5 second
Tamper	Yes
Scan distance	12 in (30 cm) - 31 in (80 cm)
TCP/IP	Yes (Static IP/DHCP (Client))
Integrated Reader	SECTOR / CSN for MiFARE Classic / Plus / DESFire EV1/2/3 (RBH-BFR-FACE-D for sector & RBH-BFR-FACE-S for CSN)
Communication data	
Communication method	TCP/IP, Weigand, OSDP ver. 1 & 2
Communication environment	LAN / WAN
Ethernet Interface	10/100M Base-T, Auto Crossover
Indication data & User interface	
Buzzer	Single Tone
TFT Color LCD	4.3 inches touch screen
Anti-Tampering switch	Yes
Electrical data conditions	
Operation voltage	12V DC / 1.5A
Operation temperature	32°F (0°C) - 122° F (50°C)
Operation humidity	10% - 80%RH
Physical data	
Dimensions	4.8 x 6.5 x 2.8 inc (123 x 166 x 72 mm)
Weight	1.4 lb (650 gr)

*Forthcoming

Order:


RBH-BFR-FACE15-D for sector
RBH-BFR-FACE15-S for CSN



RBH Access Technologies, Inc.
2 Automatic Road, Suite 108
Brampton ON L6S 6K8, Canada

1-905-790-1515
1-905-790-3680

info@rbh-access.com



www.rbh-access.com